

Roller / Scooter

Reifengröße/ Tire size/ Dimension du pneu		Profil/ Pattern/ Profil/	Max. Trag- fähigkeit/ load capa- city/ capacité de charge (kg)	Min. Luftdruck bei max. Trag- fähigkeit/ Min. air pressure at max. load capacity/ Pression de gonflage min. à capacité de charge max. (bar)	Continental Schlauch/ Tube/ Chambre à air	Felgen- breite/ Rim width/ Largeur de jante	Reifenmaße/Tire dimensions/Dimensions du pneu (mm)				
							Max. in Betrieb/in service/en service		Neu/New/À neuf		
							Breite/ Overall width/ Largeur hors tout	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Querschnitts- breite/ Section width/ Largeur du boudin	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Abrollum- fang/Rolling circum- ference/ Circon- férence de roulement
3.50 - 8 M/C 46J	TT	LB LB WW	170	2.5	D 8	2.15 2.50	99	397	92	386	1154
4.00 - 8 M/C 55J	TT	LB LB WW	218	2.5	D 8	2.15 2.50 2.75 3.00	113	427	105	415	1241
4.00 - 8C M/C 66J	TL	LB	300	3.5	D 8	2.15 2.50 2.75 3.00	113	427	105	415	1241
3.00 - 10 M/C 50J	TT	K62 K62 WW ContiClassic	190	3.25	D 10	1.85 2.15 2.50	86	422	80	413	1235
3.00 - 10 M/C 50M	TL	ContiTwist	190	3.25	D 10	1.85 2.15 2.50	86	422	80	413	1235
3.50 - 10 M/C 59J	TL	K62 K62 WW	243	3.25	D 10	2.15 2.50	99	448	92	437	1307
3.50 - 10 M/C 59L	TT	ContiClassic	243	3.25	D 10	2.15 2.50	99	448	92	437	1307
3.50 - 10 M/C 59L	TL	ContiScooty	243	3.25	D 10	2.15 2.50	99	448	92	437	1307
3.50 - 10 M/C 59M	TL	ContiTwist ContiTwist Sport	243	3.25	D 10	2.15 2.50	99	448	92	437	1307
3.50 - 10 M/C 59P	TL	ContiTwist Race	243	3.25	D 10	2.15 2.50	99	448	92	437	1307
4.00 - 10 M/C 69J	TT	K62 K62 WW	325	3.5	D 10	2.15 2.50 2.75 3.00	117	478	108	466	1393
90/90 - 10 M/C 50M	TL	ContiTwist	190	2.5	D 10	1.85 2.15 2.50	97	428	90	416	1244
90/100 - 10 M/C 53J	TL	ContiTwist	206	2.5	D 10	1.85 2.10 2.50	97	446	90	434	1298
100/80 - 10 M/C 58L	TL	ContiScooty	206	2.5	D 10	2.15 2.50 2.75	109	426	101	414	1238
100/80 - 10 M/C 58M	TL	ContiTwist	206	2.5	D 10	2.15 2.50 2.75	109	426	101	414	1238
100/90 - 10 M/C 56M	TL	ContiTwist	224	2.5	D 10	2.15 2.50 2.75	109	444	101	434	1298
100/90 - 10 M/C 61J	TL	ContiScooty	224	2.5	D 10	2.15 2.50 2.75	109	444	101	434	1298
110/80 - 10 M/C 63L	TL	ContiTwist	272	3.0	D 10	2.15 2.50 2.75 3.00	118	442	109	430	1286
120/70 - 10 M/C 54L	TL	ContiTwist	212	2.8	D 10	2.75 3.00 3.50 3.75	132	434	122	422	1262
120/90 - 10 M/C 57J	TL	ContiTwist	224	1.75	D 10	2.50 2.75 3.00	129	486	119	470	1405
120/90 - 10 M/C 57L	TL	ContiTrailly	224	1.75	D 10	2.50 2.75 3.00	129	486	119	470	1405

Roller / Scooter

Reifengröße/ Tire size/ Dimension du pneu		Profil/ Pattern/ Profil/	Max. Trag- fähigkeit/ load capa- city/ capacité de charge (kg)	Min. Luftdruck bei max. Trag- fähigkeit/ Min. air pressure at max. load capacity/ Pression de gonflage min. à capacité de charge max. (bar)	Continental Schlauch/ Tube/ Chambre à air	Felgen- breite/ Rim width/ Largeur de jante	Reifenmaße/Tire dimensions/Dimensions du pneu (mm)				
							Max. in Betrieb/in service/en service		Neu/New/À neuf		
							Breite/ Overall width/ Largeur hors tout	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Querschnitts- breite/ Section width/ Largeur du boudin	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Abrollum- fang/Rolling circum- ference/ Circon- férence de roulement
130/70 - M/C 10 59M	TL	ContiTwist	243	2.8		3.00 3.50 3.75 4.00	139	448	129	436	1301
130/90 - 10 M/C 61J	TL	ContiTwist	257	1.75	D 10	2.50 2.75 3.00 3.50	139	504	129	488	1459
130/90 - 10 M/C 61L	TL	ContiTraily	257	1.75	D 10	2.50 2.75 3.00 3.50	139	504	129	488	1459
110/70 - 11 M/C 45M	TL	ContiTwist	165	2.3		2.50 2.75 3.00 3.50	119	443	110	433	1295
3.00 - 12 M/C 47J	TT	LB LB WW	175	2.5	D 12	1.85 2.15 2.50	86	473	80	464	1387
110/70 - 12 M/C 47L	TL	ContiTwist	175	2.3		2.50 2.75 3.00 3.50	119	169	110	459	1372
110/90 - 12 M/C 64P	TL	ContiTwist	280	2.5		2.15 2.50 2.75 3.00	118	517	109	503	1504
120/70 - 12 M/C 51P	TL	ContiTwist Race ContiScooty	195	2.3		2.75 3.00 3.50 3.75	132	485	122	473	1414
120/70 - 12 M/C 58P	TL	ContiTwist ContiTwist WW ContiTwist Sport	236	2.8		2.75 3.00 3.50 3.75	132	485	122	473	1414
130/70 - 12 M/C 56P	TL	ContiTwist Race ContiScooty	224	2.3		3.00 3.50 3.75 4.00	139	499	129	487	1456
130/70 - 12 M/C 62P	TL	ContiTwist ContiTwist WW ContiTwist Sport	265	2.8		3.00 3.50 3.75 4.00	139	499	129	487	1456
140/70 - 12 M/C 65P	TL	ContiTwist	290	2.8		3.50 3.75 4.00 4.25 4.50	152	515	141	501	1498
110/90 - 13 M/C 56Q	TL	ContiTwist	224	2.3		2.15 2.50 2.75 3.00	120	542	109	528	1595
130/60 - 13 M/C 60L	TL	ContiScooty	206	2.3		3.00 3.50 3.75 4.00	142	496	129	486	1468
130/60 - 13 M/C 53P	TL	ContiTwist ContiTwist Sport	206	2.3		3.00 3.50 3.75 4.00	142	496	129	486	1468
130/70 - 13 M/C 63Q	TL	ContiTwist	272	2.3		3.00 3.50 3.75 4.00	142	524	129	512	1546

Roller / Scooter

Reifengröße/ Tire size/ Dimension du pneu	Profil/ Pattern/ Profil/	Max. Trag- fähigkeit/ load capa- city/ capacité de charge (kg)	Min. Luftdruck bei max. Trag- fähigkeit/ Min. air pressure at max. load capacity/ Pression de gonflage min. à capacité de charge max. (bar)	Continental Schlauch/ Tube/ Chambre à air	Felgen- breite/ Rim width/ Largeur de jante	Reifenmaße/Tire dimensions/Dimensions du pneu (mm)				
						Max. in Betrieb/in service/en service		Neu/New/À neuf		
						Breite/ Overall width/ Largeur hors tout	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Querschnitts- breite/ Section width/ Largeur du boudin	Außen- durchmesser/ Overall diameter/ Diamètre extérieur	Abrollum- fang/Rolling circum- ference/ Circon- férence de roulement
140/60 - 13 M/C 63S	TL	ContiTwist	272	2.3	3.50 3.75 4.00 4.25 4.50	155	510	141	498	1504
120/70 - 14 M/C 55S	TL	ContiTwist	218	2.3	2.75 3.00 3.50 3.75	134	536	122	524	1583
140/60 - 14 M/C 64S	TL	ContiTwist	280	2.8	3.50 3.75 4.00 4.25 4.50	153	536	139	524	1583
140/70 - 14 M/C 68S	TL	ContiTwist	315	2.8	3.50 3.75 4.00 4.25 4.50	153	566	139	552	1667
150/70 - 14 M/C 66S	TL	ContiTwist	355	2.3	3.50 3.75 4.00 4.25 4.50	166	580	151	566	1709
120/70 - 15 M/C 56S	TL	ContiTwist	224	2.3	2.75 3.00 3.50 3.75	134	561	122	549	1658
110/70 - 16 M/C 52S	TL	ContiTwist	200	2.3	2.50 2.75 3.00 3.50	121	570	110	560	1691
140/70 - 16 M/C 65S	TL	ContiTwist	290	2.3	3.50 3.75 4.00 4.25 4.50	153	616	139	602	1818